Перейти к продукции

TL-D Standard Colours

TL-D 36W/54-765 1SL

TL-D Standard Colors lamps (tube diameter of 26 mm) create atmospheres from warm white to cool daylight. Lamps with moderate efficacy and color rendering.

Product data

- General Characteristics

Cap-Base	G13 [Medium Bi-Pin Fluorescent]
Bulb	T8 [26 mm]
Life to 10% failures EM	10000 hr
Life to 50% failures EM	13000 hr

- Light Technical Characteristics

Color Code	54-765
Color Rendering Index	72 Ra8
Color Designation (text)	Cool Daylight
Color Temperature	6200 K
Luminous Flux Lamp EM	2500 Lm
Luminous Flux Lamp EM 30°C	2300 Lm
Lumen Maintenance 2000h	90 %
Lumen Maintenance 5000h	80 %
Lumen Maintenance 10000h	75 %
Lumen Maintenance 15000h	70 %
Luminance Average EM	0.95 cd/cm2
Chromaticity Coordinate X	315 -
Chromaticity Coordinate Y	341 -

- Electrical Characteristics

Lamp Wattage	36 W
Lamp Wattage EM	36.0 W
Lamp Voltage	103 V
Lamp Current EM	0.440 A
Dimmable	Yes

- Environmental Characteristics

Energy Efficiency Label (EEL)	B
Mercury (Hg) Content	8.0 mg

- Product Dimensions

Base Face to Base Face A	1199.4 (max) mm
Insertion Length B	1204.1 (min), 1206.5 (max) mm
Overall Length C	1213.6 (max) mm
Diameter D	28 (max) mm

- Product Data

Order code	928048505453
Full product code	928048505453
Full product name	TL-D 36W/54-765 1SL
Order product name	TL-D 36W/54-765 1SL/25
Pieces per pack	1
Packing configuration	25
Packs per outerbox	25
Bar code on pack - EAN1	6923410770322
Bar code on outerbox - EAN3	6923410770339
Logistic code(s) - 12NC	928048505453

PHILIPS

sense and simplicity

TL-D Standard Colours

ILCOS code	FD-36/62/2A-E-G13	Net weight per piece	0.140 kg

Dimensional drawing



TL-D 36W/54-765 1SL

Product	A (Max)	B (Min)	B (Max)	C (Max)	D (Max)
TL-D 36W/54-765	1199.4	1204.1	1206.5	1213.6	28



G13

Photometric data



Lightcolor /54-765



Lightcolor /54-765

© 2013 Koninklijke Philips Electronics N.V.
All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips Electronics N.V. or their respective owners.

www.philips.com/lighting

2013, April 2
data subject to change