

R39/R50/R63




LB-439



LB-450



LB-463



НАПРЯЖЕНИЕ
230/50Hz



IC
DRIVER
175-265 V



-40/+50



КП<5%



СРОК СЛУЖБЫ
30 000 ЧАСОВ



ГАРАНТИЯ
2 ГОДА

Артикул	Модель	Тип корпуса	Мощность, W	Эквивалент ЛОН, W	Угол свечения	Световой поток, Lm	CRI	Цветовая температура, K	Размеры Н x L, мм	Цоколь	Кол-во штук в упаковке/коробе
25516	LB-439	R39 рефлектор	5	40	120°	380	>80	2700	67 x 39	E14	10/100
25517						400		4000			
25518						420		6400			
25513	LB-450	R50 рефлектор	7	60		540		2700	80 x 50	E14	
25514						560		4000			
25515						580		6400			
25510	LB-463	R63 рефлектор	11	100		860		2700	99 x 63	E27	
25511						880		4000			
25512						900		6400			


G45



LB-38, LB-95, LB-550,
LB-750 E27



LB-95, LB-550,
LB-750 E14



НАПРЯЖЕНИЕ
230/50Hz



IC
DRIVER
175-265 V



-40/+50



КП<5%



СРОК СЛУЖБЫ
30 000 ЧАСОВ



ГАРАНТИЯ
2 ГОДА

Артикул	Модель	Тип корпуса	Мощность, W	Эквивалент лампы накаливания, W	Угол свечения	Световой поток, Lm	CRI	Цветовая температура, K	Размеры Н x L, мм	Цоколь	Кол-во штук в упаковке/коробе
25404	LB-38*		5	50	220°	410	>80	2700	82 x 45	E27	10/100
25405						420		4000			
25478						560		2700			
25479	LB-95		7	70		580		4000	E14		
25480						600		6400			
25481						560		2700			
25482	LB-550	G45 шарик	9	90		580		4000	E27		
25483						600		6400			
25801						800		2700			
25802	LB-550	G45 шарик	9	90	820	4000	E14				
25803					840	6400					
25804					800	2700					
25805	LB-750		11	110	820	4000	E27				
25806					840	6400					
25946					915	2700					
25947	LB-750		11	110	935	4000	E14				
25948					955	6400					
25949					915	2700					
25950	LB-750		11	110	820	4000	E27				
25951					955	6400					