



---

# Техническое описание продукта

## P RF CLAS A 7.5 W/840 E27

PARATHOM Retrofit CLASSIC A | Светодиодные лампы, классической грушевидной формы



## Техническое описание продукта

### Technical data

#### Электрические параметры

ZLDV_Rated wattage [AGGR]	7.50 W
ZLDV_Nominal wattage [AGGR]	7.50 W
ZLDV_Nominal voltage [AGGR]	220...240 V
ZLDV_Operating frequency [AGGR]	50...60 Hz
ZLDV_Max. lamp no. on circuit break. 10 A (B) [AGGR]	81
ZLDV_Max. lamp no. on circuit break. 16 A (B) [AGGR]	131
ZLDV_Nominal current [AGGR]	0.061 A
ZLDV_Claimed equiv. conventional lamp power [AGGR]	75 W


#### Фотометрические данные

ZLDV_Nominal luminous flux [AGGR]	1055 lm
ZLDV_Rated luminous flux [AGGR]	1055 lm
ZLDV_Rated color temperature [AGGR]	4000 K
ZLDV_Color rendering index Ra [AGGR]	≥80
ZLDV_Light color (designation) [AGGR]	Cool White
ZLDV_Standard deviation of color matching [AGGR]	≤6 sdcn
ZLDV_Color temperature [AGGR]	4000 K
ZLDV_Luminous flux [AGGR]	1055 lm
ZLDV_Lumen main.fact.at end of nom.life time [AGGR]	0.70

#### Светотехнические параметры

ZLDV_Beam angle [AGGR]	300.00 °
ZLDV_Starting time [AGGR]	< 0.5 s

#### Размеры и вес



ZLDV_Overall length [AGGR]	105.0 mm
----------------------------	----------

## Техническое описание продукта

ZLDV_Diameter [AGGR]	60.0 mm
ZLDV_Outer bulb [AGGR]	A60
ZLDV_Product weight [AGGR]	34.00 g
ZLDV_Length [AGGR]	105.0 mm

### Температуры и условия управления

ZLDV_Ambient temperature range [AGGR]	-20...+40 °C
---------------------------------------	--------------

### Срок службы

ZLDV_Nominal lamp life time [AGGR]	15000 h
ZLDV_Rated lamp life time LEDr [AGGR]	15000 h
ZLDV_Number of switching cycles [AGGR]	100000
ZLDV_Lumen maintenance at end of service life [AGGR]	0.70

### Дополнительные данные

ZLDV_Base (standard designation) [AGGR]	E27
ZLDV_Mercury content [AGGR]	0.0 mg
ZLDV_Mercury-free [AGGR]	Yes
ZLDV_Design / version [AGGR]	frosted
Утилизация по WEEE	Да
ZLDV_Product remark [AGGR]	All technical parameters apply to the entire lamp/Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value

### Возможности / мощности

ZLDV_Dimmable [AGGR]	No
----------------------	----

### Сертификаты и Стандарты

ZLDV_Energy efficiency class [AGGR]	A++
ZLDV_Energy consumption [AGGR]	8 kWh/1000h
ZLDV_Type of protection [AGGR]	IP20

### Классификация

ZLDV_ILCOS [AGGR]	DRAA/F-8/840-220-240-E27-60
ZLDV_Order reference [AGGR]	LEDPCA75 7,5W/

### Environmental information

Техническое описание продукта

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	18-04-2022
Primary Article Identifier	4058075287563   4058075591578
Declaration No. in SCIP database	In work

Ecodesign regulation information:

Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Данные для заказа

Product code	Описание продукта	Упаковка (цена/шт.)	Размеры (длина x ширина x высота)	Объем	Вес брутто
4058075591578	P RF CLAS A 7.5 W/840 E27	Shipping carton box 10 шт. Folding carton box	315 mm x 131 mm x 126 mm	5.20 дм³	544.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Примечание

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

OSRAM is distribution partner of LEDVANCE of LAMPS

OSRAM

OSRAM GmbH  
Marcel-Breuer-Strasse 6  
80807 Munich, Germany